

Hohlstahl DIN 17456 / 17458

warmgewalzt / stranggepreßt, gebeißt

Herstellungslänge 2 - 7 m

Abnahmeprüfzeugnis DIN 50049/3.1B bzw. EN 10204/3.1B

Abmessung mm	Gewicht - 0 / + 20% kg/m	W.-Nr.	
		4301 / 4306 304 / 304 L	4571
32 x 16	4,70	x	x
20	3,80	x	x
36 x 16	6,40	x	x
20	5,50	x	x
25	4,10	x	x
40 x 20	7,40	x	x
25	6,00	x	x
28	5,00	x	x
45 x 20	10,00	x	x
25	8,90	x	x
28	7,60	x	x
32	6,20	x	x
50 x 25	11,60	x	x
32	9,10	x	x
36	7,40	x	x
56 x 28	14,50	x	x
36	11,30	x	x
40	9,50	x	x
60 x 40	12,30	x	x
44	10,40	x	x
63 x 32	18,10	x	x
36	16,50	x	x
40	14,60	x	x
45	12,00	x	x
50	9,10	x	x
70 x 50	15,02	x	x
71 x 36	23,10	x	x
40	21,20	x	x
45	18,60	x	x
56	11,70	x	x
75 x 40	24,80	x	x
76 x 58	15,09	x	x
80 x 40	29,60	x	x
45	27,00	x	x
50	24,00	x	x
63	15,00	x	x
85 x 45	32,00	x	x
90 x 50	34,50	x	x
56	30,60	x	x
63	25,50	x	x
71	18,80	x	x
95 x 50	40,90	x	x
100 x 56	42,30	x	x
63	37,20	x	x
71	30,60	x	x
80	22,20	x	x
106 x 56	49,90	x	x
63	44,80	x	x
71	38,20	x	x
80	29,80	x	x

Abmessung mm	Gewicht - 0 / + 20% kg/m	W.-Nr.	
		4301 / 4306 304 / 304 L	4571
112 x 63	52,80	x	x
71	46,20	x	x
80	37,80	x	x
90	27,40	x	x
118 x 63	61,30	x	x
71	54,70	x	x
80	46,30	x	x
90	35,90	x	x
125 x 71	65,20	x	x
80	56,80	x	x
90	46,40	x	x
100	34,60	x	x
132 x 71	76,30	x	x
80	67,90	x	x
90	54,40	x	x
106	38,10	x	x
140 x 80	81,30	x	x
90	70,80	x	x
100	59,10	x	x
112	43,50	x	x
150 x 80	99,20	x	x
95	84,35	x	x
106	69,40	x	x
125	42,30	x	x
160 x 90	109,55	x	x
112	80,40	x	x
122	67,10	x	x
132	50,50	x	x
170 x 106	110,60	x	x
118	92,20	x	x
130	73,90	x	x
140	57,30	x	x
180 x 125	103,30	x	x
130	97,03	x	x
150	61,00	x	x
190 x 106	155,65	x	x
123	129,30	x	x
132	115,00	x	x
140	107,70	x	x
150	83,80	x	x
160	64,70	x	x
200 x 140	127,70	x	x
150	109,60	x	x
160	90,20	x	x
212 x 130	175,60	x	x
150	138,00	x	x
170	100,50	x	x
224 x 140	191,00	x	x
180	111,30	x	x
236 x 150	207,80	x	x
190	122,70	x	x
240 x 170	177,00	x	x
250 x 200	140,90	x	x

Andere Abmessungen oder Werkstoffe auf Anfrage.

